

Safety data sheet

Revision: 23-05-2018
Replaces: 15-02-2017
Version: 03.00/GBR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: BERA-FIX solder paste

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Soldering and tinning.

1.3. Details of the supplier of the safety data sheet

Supplier: Boliden Bergsøe A/S
Hvissingevej 116
2600 Glostrup
Denmark
Tel: +45 43268300
Fax: +45 43268301
Email: metal.glostrup@boliden.com

1.4. Emergency telephone number

0870 600 6266 (UK only) Only available to health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification (Regulation (EC) No 1272/2008): Skin Corr. 1B; H314 Aquatic Chronic 1; H410 Eye Dam. 1; H318 STOT SE 3; H335 Repr. 1A; H360FD STOT RE 1; H372 Lact.; H362 Aquatic Acute 1; H400

Please see section 16 for the full text of H-phrases.

Most serious harmful effects: Causes severe skin burns and eye damage. Very toxic to aquatic life with long lasting effects. Causes serious eye damage. May cause respiratory irritation. May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause harm to breast-fed children. Very toxic to aquatic life. Harmful if vapours from molten metal are inhaled or if the skin comes in contact with molten metal.

2.2. Label elements



Signal word:

Danger

Contains:

Zinc chloride; Lead

H-phrases:

Causes severe skin burns and eye damage.(H314)
Very toxic to aquatic life with long lasting effects.(H410)
May cause respiratory irritation.(H335)
May damage fertility. May damage the unborn child.(H360FD)

Causes damage to organs through prolonged or repeated exposure.(H372)
 May cause harm to breast-fed children.(H362)

P-phrases: Obtain special instructions before use.(P201)
 Wear protective gloves/protective clothing/eye protection/face protection.(P280)
 IF SWALLOWED: Immediately call a POISON CENTER/doctor.(P301/310-a)
 IF exposed or concerned: Get medical advice/attention.(P308/313)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305/351/338)
 Immediately call a POISON CENTER/doctor.(P310-a)
 Dispose of contents/container in accordance with local regulation.(P501-A)

Supplemental information: Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.
 Restricted to professional users.

2.3. Other hazards

(PBT/vPvB) No assessment required, as the product contains inorganic matter only.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Registration number	CAS/EC Number	Substance	CLP-classification (Regulation (EC) No 1272/2008)	w/w%	Note
.	7439-92-1-F 231-100-4	Lead	Repr. 1A;H360FD Lact.;H362 STOTRE 1;H372 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	20-60	.
.	7440-31-5 231-141-8	Tin	.	12,5-50	.
01-211947243 1-44-	7646-85-7-d 231-592-0	zinc chloride	Acute Tox. 4;H302 Skin Corr. 1B;H314 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	10-15	.
.
.

Please see section 16 for the full text of H-phrases.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Seek medical advice immediately.

Skin: Immediately remove contaminated clothing, watch and jewellery. Wash the skin thoroughly with water and continue washing for a long time. Seek medical advice immediately.

Eyes: Open eye wide, remove any contact lenses and flush immediately with water (preferably using eye wash equipment). Seek medical advice immediately. Continue flushing until medical attention is obtained.

Other information: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Has a caustic burning effect and causes burning pain, reddening, blistering and burning sores if it comes in contact with skin. Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids. Risk of serious eye injury and loss of sight. Inhalation is irritating to the upper airways. Harmful if vapours from molten metal are inhaled or if the skin comes in contact with molten metal. Causes damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child. May cause harm to breast-fed children.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. Ensure that medical personnel are aware of the material involved, and take precautions to protect themselves.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing media Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is not directly flammable. Avoid inhalation of vapour and fumes – seek fresh air.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit. Extinguishing water which has been in contact with the product may be corrosive.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: In case of insufficient ventilation, wear respiratory protective equipment. Wear safety goggles/face protection. Wear gloves. Stay upwind/keep distance from source. Stop leak if this can be done without risk.

For emergency responders: In addition to the above: Chemical protective suit equivalent to EN 943-2 is recommended.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers. Wipe up minor spills with a cloth. Caution! Causes burns.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk when breastfeeding. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Store in a dry, cool, well-ventilated area. Keep in tightly closed original packaging. Private users must keep the product under lock. This requirement does not apply to commercial use.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Ingredient:	Exposure limit	Comments
zinc chloride	- (8h), - (15m) ppm	Fume
.	1 (8h), 2 (15m) mg/m ³	.
Lead	- (8h), - (15m) ppm	.
.	0.15 (8h), - (15m) mg/m ³	.
Tin	- (8h), - (15m) ppm	.
.	2 (8h), 4 (15m) mg/m ³	.

Legal basis: EH40/2005 Workplace exposure limits. Last amended December 2011.

Measuring methods: Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles/face protection. Eye protection must conform to EN 166.

Personal protective equipment, skin protection: Wear plastic or rubber protective gloves. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374. Wear protective gloves which protect against contact and splashing from molten metal. Gloves must conform to EN 12477.

Personal protective equipment, In case of heating/use of the product in an area with inadequate ventilation, wear respiratory

respiratory protection: protection with filter B/P3. Respiratory protection must conform to one of the following standards: EN 136/140/145.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Paste
Colour:	Grey
Odour:	Prickling
Odour threshold:	No data
pH (solution for use):	No data
pH (concentrate):	No data
Melting point/freezing point:	183-238°C
Initial boiling point and boiling range:	No data
Flash point:	No data
Evaporation rate:	No data
Flammability (solid, gas):	No data
Upper/lower flammability limits:	No data
Upper/lower explosive limits:	No data
Vapour pressure:	No data
Vapour density:	No data
Relative density:	7
Solubility:	Soluble in the following: Water.
Partition coefficient n-octanol/water:	No data
Auto-ignition temperature:	No data
Decomposition temperature:	No data
Viscosity:	No data
Explosive properties:	No data
Oxidising properties:	No data

9.2. Other information

None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Not reactive.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral:	The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Ingestion of large quantities may cause discomfort. 7646-85-7-d: Rat: LD50 = 350 mg/kg
Acute toxicity - dermal:	The product does not have to be classified. Test data are not available.
Acute toxicity - inhalation:	The product does not have to be classified. Test data are not available.
Skin corrosion/irritation:	Has a caustic burning effect and causes burning pain, reddening, blistering and burning sores if it comes in contact with skin.

Serious eye damage/eye irritation:	Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids. Risk of serious eye injury and loss of sight.
Respiratory sensitisation or skin sensitisation:	The product does not have to be classified. Test data are not available.
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.
Carcinogenic properties:	The product does not have to be classified. Test data are not available.
Reproductive toxicity:	May damage fertility. May damage the unborn child. May cause harm to breast-fed children.
Single STOT exposure:	Inhalation is irritating to the upper airways. Inhalation of smoke from the soldering / welding process may cause irritation to the upper airways. May cause a burning sensation in the nose, mouth and throat, as well as headaches, coughing and discomfort.
Repeated STOT exposure:	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard:	The product does not have to be classified. Test data are not available.
Other toxicological effects:	Inhalation of lead vapors can cause accumulation of lead in the body. Accumulation of large quantities may cause discomfort as memory loss, paralysis, insomnia and kidney problems. Ingestion may cause caustic burning in mouth, oesophagus and stomach. Pains in mouth, throat and stomach. Difficulty swallowing, feeling unwell and vomiting of blood. Brown spots and burns may appear in and around the mouth.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The concept of biodegradability is not relevant, as the product contains inorganic matter only.

12.3. Bioaccumulative potential

No bioaccumulation expected.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Avoid discharge to drain or surface water. If this product as supplied becomes a waste, it meets the criteria of a hazardous waste (Dir. 2008/98/EU). Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site.

EWC code: Depends on line of business and use, for instance 16 03 03* inorganic wastes containing dangerous substances

Absorbent/cloth contaminated with the product:

EWC code: 15 02 02 absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances

Empty, cleansed packaging should be disposed of for recycling. Uncleansed packaging is to be disposed of via the local waste-removal scheme.

SECTION 14: Transport information**ADR/RID**

14.1. UN number	1759
14.2. UN proper shipping name	CORROSIVE SOLID, N.O.S. (Zinc chloride)
14.3. Transport hazard class(es)	8
14.4. Packing group	III
Hazard identification number	80
Tunnel restriction code:	E
14.5. Environmental hazards	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.

ADN

14.1. UN number	1759
14.2. UN proper shipping name	CORROSIVE SOLID, N.O.S. (Zinc chloride)
14.3. Transport hazard class(es)	8
14.4. Packing group	III
14.5. Environmental hazards	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
Transport in tank vessels:	Not applicable.

IMDG

14.1. UN number	1759
14.2. UN proper shipping name	CORROSIVE SOLID, N.O.S. (Zinc chloride)
14.3. Transport hazard class(es)	8
14.4. Packing group	III
14.5. Environmental hazards	The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l.

IMDG Code segregation group: 1 - Acids

ICAO/IATA

14.1. UN number	1759
14.2. UN proper shipping name	CORROSIVE SOLID, N.O.S. (Zinc chloride)
14.3. Transport hazard class(es)	8
14.4. Packing group	III
14.5. Environmental hazards	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.

14.6. Special precautions for user

None.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

Covered by: Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 92/85/EEC of 19 October 1992 on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.
The product is comprised by Regulation 1907/2006/EC, Annex XVII concerning restrictions.

Directive 2012/18/EU (Seveso), E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1: Column 2: 100 t, Column 3: 200 t.

15.2. Chemical safety assessment

Chemical safety assessment has not been performed.

SECTION 16: Other information

Changes have been made in the following sections: 1,2,3,4,8,11,12,13,15,16

Abbreviation explanations: PBT: Persistent, Bioaccumulative and Toxic
vPvB: Very Persistent and Very Bioaccumulative
STOT: Specific Target Organ Toxicity

Classification method: Calculation based on the hazards of the known components.

H-phrases: H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Training: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Other information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

HSV/ Bureau Veritas HSE Denmark A/S Oldenborggade 25-31, DK-7000 Fredericia T: +45 77 31 10 00, E-mail: infohse@dk.bureauveritas.com, Web: www.hse.bureauveritas.dk (Made in Toxido®)
UK